



# DOUBLE GAS PLUG™ STAINLESS STEEL

- WEATHER DURABLE BRUSHED STAINLESS STEEL ENCLOSURE
- DIRECT CONNECTION TO EXISTING LOW PRESSURE OR 2# RESIDENTIAL GAS SYSTEMS FOR INDOOR/OUTDOOR USE
- THERMAL VALVE SHUTS OFF GAS FLOW IN CONDITIONS OF 300°F OR MORE
- ALSO AVAILABLE WITHOUT 90° ELBOW FOR BOTTOM INLET CONNECTION
- CLEAN, COMPACT DESIGN, CONCEALS UNSIGHTLY PIPES AND VALVES
- **2-3/8" KWIK DISCONNECT SAFETY SHUT-OFFS WITH EASY ACCESS**
- C/W ADJUSTABLE STANDOFFS FOR SIDING INSTALLATIONS

Model G0101-DBL-SS

Model G0101-2#DBL-SS

THE IDEAL METHOD OF CONNECTING MULTIPLE BARBEQUES, PATIO HEATERS, ETC. THIS UNIT IS THE ULTIMATE IN AN OUTDOOR GAS CONNECTION DESIGNED WITH A 1/2" INLET TO PROVIDE AMPLE CAPACITY TO SERVICE ALL YOUR OUTDOOR APPLIANCES.

## SPECIFICATIONS

### Capacity:

Model G0101-DBL-SS 60,000 BTU (NG) each side  
90,000 BTU (LP) each side

Model G0101-2#-DBL-SS 60,000 BTU (NG) each side

Inlet Connection: 1/2" NPT Rear/Bottom

Hose Connection: (2)-3/8" Kwik Disconnect

Overall Size: G0101-DBL-SS - 7" x 5 1/4" x 2 1/4"

G0101-2#DBL-SS - 8" x 5 1/4" x 2 1/4"

Approved for temperatures to -40 deg.



**WHY FILL UP  
WHEN YOU  
CAN HOOK UP**



Distributed by:



0.. - 4 / 0 # /  
- t  
. - OGP CCN GHDPN t # CCNGHDPN