



ASSEMBLY INSTRUCTIONS SINGLE HEAD TIKI STAND

PROPANE

Tools Required

1/8" Allen Wrench (supplied)
2 – Pipe Wrenches
Expandable Wrench
Soap Test Solution

Assembly of Portable Propane Single Head Tiki Stand

Remove all components from the packaging and check against list of components in the box. Report any missing items to supplier immediately.

Install 1 ½" x 22" Pipe on to base using a pipe wrench to firm the pipe to Flange connection. The strap loop and hook should face the center of the base. No pipe dope is necessary on this connection.

Join the 1" x 25 ½" Pipe assembly and the 1" x 48" Pipe USING PIPE DOPE, OR AN APPROVED TEFLON TAPE. Tighten firmly using pipe wrenches.

Install Regulator and hose assembly on to 3/8" Flare Fitting on 1" x 25 ½" pipe assembly. Install a cap on the 1" pipe and hook complete assembly on to the L.P. Tank. Soap test all gas joints for leakage.

Note** This work should be carried out by a "Qualified Gas Fitter". Even though the 1" x 25 ½" Pipe assembly has been pressure tested after assembly in the plant, the joints may have been loosened during shipping and ALL joints will be the responsibility of the "Gas Fitter" to check.

Remove 1" cap and disconnect hose assembly, making sure the "TANK VALVE IS OFF FIRST"

Insert the complete assembly into the 1 ½" pipe on the base.

Tighten set screws in 1 ½" pipe with the Allen wrench supplied.

Install the Tiki Head on the 1" pipe using pipe dope and securing with pipe wrenches.

Place the tank on the base with the base in the 9" retaining ring provided.

Hook one end of the tie down strap on the bottom hook of the 1 ½" x 22" pipe installed on the base. Loop the other end through the top ring on the same pipe, then through the handle portion of the Propane Tank.

Secure the opening brass "D" ring of the other half of the tie down strap to the base via the thumb screw on the tank ring.

Pull firmly on both ends of each tie down strap and Velcro the two halves together.

Make sure the tank is secure to base and pipe assembly.

Use the Tank cover to hide the propane tank.

Holding your ignition source to the burner on the Tiki cone, turn on the tank valve slowly. If the Tiki head does not ignite within 3 seconds, turn off the tank valve and wait for 3-5 minutes before trying again.

Note** There should be no flash back on, or after ignition. If there is, there is a problem and the unit should be returned to the manufacturer.

Every Tiki Head is test fired in the plant before shipment.

A final soap test of the Tiki Head to pipe connection should be done when the Tiki Head is ignited.

Please read the Safety and Service instruction that comes with each Tiki Head.

"Enjoy the Ambience"