



NOTES :

1. RATED AMBIENT TEMPERATURE -40°F TO 225°F
2. INLET PRESSURE RANGE: 1/2PSI-2PSI
3. MAX FLOW RATE : 250000BTU/Hr
4. OUTLET PRESSURE RANGE : INLET PRESSURE 2psi,
OUTLET PRESSURE IS SET TO 7 ± 0.3 , CAN BE ADJUSTED TO 4"-11"
5. LEAKAGE RATE FOR REGULATOR SHOULD BE LESS THAN 0.33mL/min
AT 21Kpa AIR PRESSURE
6. BALL CHECK LIMITING DEVICE SHOULD BE INSTALLED UPWARD
7. FOR INDOOR USE VENT LIMIT
8. FOR OUTDOOR USE PLASTIC COVER

GR250C2P06	Plastic Cover	OUTDOOR
GR250C2P05	Vent Limit	INDOOR
PART NO.	A	USE

	日期 DATE	記事 MEMO	
標記 MARK		規格 SPEC	品名 DESCRIPTION
		表面處理 FINISH	關係 RELATION
		品番 PART NO.	比例 RATIO
		日期 DATE	機種 MODEL
		GR250C2P	4 MM/ 5MM
		2018.09.18	

承認 APPROVER	審查 EXAM	檢圖 CHECK	設計 DESIGNER	制圖 DRAWER	一般公差 TOLERANCE		材質(編號) MATERIAL(#.)
	HuiChen			LiangLi	尺寸範圍 LIMIT	容許差 TOLANCE	版本 DRAW NO.
					0-9	±0.1	A
					10-50	±0.15	視圖 Angle of view
					51-250	±0.25	
					251-1000	±1.0	
					≥1000	±1.50	
					角度Angles	±1°	

寧波金歐五金制品有限公司
KIN-OU NINGBO JINOU HARDWARE CO.,LTD.